Trade Scales Limited

Ishida Compact Weighing Systems

<u>IPC</u>

Features

Compact & Versatile

The IPC is a portable scale with a compact design. It allows users to measure weights of items from 1 g to 30 kg.

Dual Power Operation

Use IPC with an AC adaptor (optional) or batteries (sold separately) depending on usage. Two alkaline batteries allow an operation as long as 500 hours, and an indicator lets you know when to change batteries. Auto Power Off function saves power and ensures long battery life.

Large Display Panel

The LCD panel is large and positioned at an angle for easy viewing to prevent misreading. A dual display (front and back) model is also available on order.



Specifications

Model	Small		
Platter size	230 x 200 mm		
	Approval type	Non approval type	
Capacity and minimum graduation	3kg/1g(0~1.5kg), 2g(1.5~3kg) 6kg/2g(0~3kg), 5g(3~6kg)	3kg/1g 6kg/2g	
Weighing method	Electric resistance method		
LCD panel	Six digits(7-segment), character height 25 mm		
Display information	6-digit weight, battery indicator, decimal point, net weight indicator, stability indicator, minus sign, and unit of measurement		
Net weight measurement	Subtraction of tare weight by key input		
Power	Dry Cell 2 pieces (can be operated for 500 hours with alkaline dry D- Type batteries) or AC Adaptor (No Dry Cell and/or AC adaptor are included in the shipment) Auto Power Off function (can be set to 60 min., 20 min., or off)		
Operational temperature	-5°C ~ 40°C		
Outer dimensions (W x D x H)	236 x 282 x 100 mm		
Weight	2.0kg (excluding batteries)		
Approvals	OIML,CE conformity for approval type		

Trade Scales Limited PO Box 54-062, The Marina, Manukau 2144 Phone +64 9 537 4776, Fax +64 9 537 4778, Web www.tradescales.co.nz





Trade Scales Limited

Model	Large		
Platter size	280 x 293 mm		
	Approval type	Non approval type	
Capacity and minimum graduation	15kg/5g(0-7.5kg), 10g(7.5~15kg) 30kg/10g(0~15kg),	15kg/5g 30kg/10g	
	20g(15~30kg)		
Weighing method	Electric resistance method		
LCD panel	Six digits(7-segment), character height 25 mm		
Display information	6-digit weight, battery indicator,dicimal point, net weight indicator, stability indicator, minus sign, and unit of measurement		
Net weight measurement	Subtraction of tare weight by key in		
Power	Dry Cell 2 pieces (can be operated for 500 hours with alkaline dry D- Type batteries) or AC Adaptor (No Dry Cell and/or AC adaptor are included in the shipment) Auto Power Off function (cb be set to 60 min., 20 min., or off)		
Operational temperature	$-5^{\circ}C \sim 40^{\circ}C$		
Outer dimensions (W x D x H)	286 x 363 x 102 mm		
Weight	3.2kg (excluding batteries)		
Approvals	OIML,CE conformity for approval type		

Dimensions

