

Trade Scales Limited



Ishida Compact Weighing Systems

IPC-WP

Features

Durable Construction Equals Quality Performance

Meeting the demands of an IP-65 rating, Ishida's IPC-WP is protected from dust and low pressure water. The stainless steel platter is designed for ease, removal and frequent washing for food and chemical applications. The IPC-WP's sleek design is coupled with accuracy and user friendly operation.



On the Go Convenience

Today's fast-moving business climate demands portable solutions. Quite simply your tools need to be where you are. That's precisely why we created the IPC-WP with both battery power and an AC adapter. When required, the IPC-WP is easy to move and instantly set up at remote locations such as farmers markets and roadside stands. Two D-cell batteries allow efficient, extended operation-as long as 500 hours, and an enunciator lets you know when to change them. The IPC-WP's selectable Auto Power Off function saves power and ensures long battery life.

Large Display & Accessible Buttons

The large 25mm LCD panel provides instant weight identification and the optional dual display is ideal for retail applications. The IPC is a portable scale with a compact design. It allows users to measure weights of items from 1 g to 30 kg.



Specifications

| | |
|-------------------------------|---|
| Platter size | 229 x 196 mm |
| Capacity / minimum graduation | Multi Interval |
| | 3kg |
| | 1g(0~1.5kg), 2g(1.5~3kg) |
| | 6kg |
| | 2g(0~3kg),5g(3~6kg) |
| | 15kg |
| Weighing method | Strain gauge load cell |
| LCD panel | Six digits(7-segment),character height 25 mm |
| Display information | 6-digit weight, battery enunciator, decimal point, net weight enunciator, stability enunciator, minus sign, and unit of measurement |

Trade Scales Limited

Specifications

| | |
|-------------------------|---|
| Power | 2 Dry Cell D-Type batteries (up to 500 hours) or AC Adaptor (Dry Cell batteries and/or AC adaptor are not included) Auto Power Off function (can be set to 60 min., 20 min., or off) |
| Operational temperature | -5° ~ 40°C |
| Weight | 3.2 kg (excluding batteries) |
| Approvals | OIML,CE conformity for approval type |
| Option | AC adapter |

Dimensions

