

Trade Scales Limited

Thermal Label Printing Solutions

TSC TTP-243

Features

- 2MB flash memory and 2 MB dram memory
- Up to 76mm (3.0") per second print speed
- Ribbon capacity up to 300m (984')
- Label capacity up to 214mm od (8.4" od)
- 2-year limited warranty
- Options include stand-alone printer controller, bar code scanner, rotary Cutter, and expandable flash memory Cartridges.

In the competitive business world, you need a simple and effective solution for your bar code printing needs. The TSC TTP-243 series offers a durable design with versatile capabilities that were created to meet your diversified demands. As our best-selling line of printers, the TTP-243 series offers a plug-and-play design as well as the strongest mechanism in its class.



The TTP-243 series re-defines low volume desktop bar code printing. With the largest media/ribbon capacities, fast print speed, and large memory capacity in its class, the TTP-243 series outperforms the competition easily. These are virtually trouble-free units - once you plug it in, you won't have to worry about it.

Possible applications include shipping & receiving, compliance labelling, asset tracking, inventory control, document management, shelf-labelling & product marking, and specimen labelling & patient tracking.

Trade Scales Limited

Specifications

Printer Model	TTP-243 Plus	TTP-243E Plus	TTP-342 Plus
Resolution	203dpi	203dpi	300dpi
Printing Method	Thermal Transfer		
Print Speed	1.5, 2.0, 3.0 ips	1.5, 2.0, 3.0 ips	1.0, 1.5, 2.0 ips
Max Print Width	104 mm (4.09")		
Max. Print Length	1,016 mm (40")	1,016 mm (40")	457 mm (18")
Enclosure	ABS plastic		
Physical Dimensions	288mm (L) x 232mm (W) x 156mm (H) 11.34" (L) x 9.13" (W) x 6.14" (H)		
Label Roll Capacity	Internal: 109mm (4.3") OD External: 214mm (8.4") OD	Internal: 109mm (4.3") OD External: 214mm (8.4") OD (Optional)	Internal: 109mm (4.3") OD External: 214mm (8.4") OD
Memory	2MB Flash 2MB DRAM		
Interface	RS-232 Centronics Parallel ports		
Power	100-240V universal switching power supply		
Operation Switch/Button	Two push buttons (Pause, Feed) Three indicators LED (Power, Error, On line)		
Sensors	Transmissive Reflective Ribbon end Peel-off	Transmissive Reflective Ribbon end	Transmissive Reflective Ribbon end Peel-off
Others	Real Time Clock	N / A	Real Time Clock
Internal Font	5 alpha-numeric fonts		
Barcode	1D bar code - Code 39, Code 93, Code 128UCC, Code 128 subset A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN und UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China Post 2D bar code - PDF-417, Maxicode, DataMatrix, QR code		
Font & Barcode Rotation	0, 90, 180,270 degrees		
Printer Language	TSPL, TPLE		
Media type	Roll-fed, fan-fold, continuous, die-cut, black mark, ticket, tag		
Media Wound Type	Outside wound		
Media Width	25.4~114 mm (1.0" ~ 4.49")		
Media Thickness	0.06~0.25 mm (2.36 ~ 9.84 mil)		
Media Core Diameter	25.4~76.2 mm (1"~3")		
Environmental Conditions	Operation: 5~40 C (41 F~104 F), Storage: -10~60 C (14 F~140 F)		
Safety Regulation	CE, FCC Class A, C-Tick, BSMI, CCC, TUV/Safety		
Dealer Option	Rotary Cutter (Label thickness up to 0.20mm)	N / A	Rotary Cutter (Label thickness up to 0.20mm)
User Option	Font memory card (up to 4MB) External LAN adapter Keyboard display unit (KU-007 Plus and KP-200) Contact CCD bar code scanner Long range linear image bar code scanner Rechargeable Battery pack	Font memory card (up to 4MB) External LAN adapter Keyboard display unit (KU-007 Plus and KP-200) Contact CCD bar code scanner Long range linear image barcode scanner Rechargeable Battery pack External roll mount	Font memory card (up to 4MB) External LAN adapter Keyboard display unit (KU-007 Plus and KP-200) Contact CCD bar code scanner Long range linear image barcode scanner Rechargeable Battery pack

Trade Scales Limited

Accessories

BarTender UltraLite Edition
Labeling Software CD disk
Quick start guide
Auto switching power
supply
Parallel port cable & power
cord
Label & ribbon sample roll
Ribbon spindle x 2
Ribbon rewind paper core
Label spindle x 2
External label roll mount

BarTender UltraLite Edition
Labeling Software CD disk
Quick start guide
Auto switching power
supply
Power cord
Ribbon spindle x 2
Ribbon rewind paper core
Label spindle x 2

BarTender UltraLite Edition
Labeling Software CD disk
Quick start guide
Auto switching power
supply
Parallel port cable & power
cord
Label & ribbon sample roll
Ribbon spindle x 2
Ribbon rewind paper core
Label spindle x 2
External label roll mount

